

# VP10F7X

## 10.4" LCD POS Monitor

### Features :

10.4" TFT SVGA LCD

800\*600

220 cd/m<sup>2</sup>

400:1

Optional Touch

Optional VGA + Audio

Optional TV Tuner



### LCD Display

Display Type : 10.4" active matrix TFT LCD panel  
Pixel Pitch : 0.088(H)×0.264(V) mm  
Display Area : 211.2(H)×158.4(W) mm  
Viewing Area : L/R +55°~-55° , U/D +40°~-40°  
Brightness : 220 cd/m<sup>2</sup>  
Contrast Ratio : 400:1  
Response Time : 25ms

### Operation Features

Input Range : 30KHZ-54KHZ / 50HZ-75HZ  
Display Colors : 262.144  
Resolution : SVGA 800x600@75Hz

### Humidity and Temperature Condition

Operation : 20%~80%, 0°~45°  
Storage : 20%~80%, -20°~60°

### Features Selection

PC : Analog - 15 pin D-sub  
Video : AV1-RCK Jack, S-Jack  
Audio : Line in-stereo  
R/L Channel : RCA Jack  
Filter Type : 2D  
Touch : Capacitive/Resistive type, RS232 Connector

### User Control

Front Control : Auto Adjust, Menu, Select+, Select-,  
OSD : Brightness, Contrast, Display Adjust  
Color Temperature, Language, OSD Adjust  
Audio Control, Reset Exit

### Physical Specification

ID : Metal  
Dimension : TBD  
Weight : TBD

### Power

Power Saving : VESA DPMS Standard  
Consumption : 15W (typical)

### Regulation

Safety & EMI : UL, CSA, TUV/GS, CE, VCCI, FCC(DoC),